TO-247-4L



(Tc = 25°C unless otherwise specified)

$V_{DS,max}$	Drain source voltage	1200	V	V_{GS} = 0V, I_D = 100μA	
$V_{GS,max}$	Gate source voltage			bsolute maximum values	Note1
$V_{GSpulse}$	Gate-source voltage,max. transient voltage	10 /+25	V	≤ 0.5μs, D 0.01	
V_{GSop}	Gate source voltage	-4 /+18	V	commended operational values	
I_D	Continuous drain current	65	A	$_{GS}$ = 18V, T_C = 25˚C	Fig.19
		46		V_{GS} = 18V, T_C = 100˚C	
$I_{D(pulse)}$	Pulsed drain current	185	A	Pulse width t_P =100μS limited by $T_{J,max}$	Fig.22
P_D	Power dissipation	268	W	T_C = 25˚C,T_J = 175˚C	Fig.20
T_J ,T_{stg}	Operating Junction and storage temperature	-55 to +175	˚C		
T_L	Soldering temperature	260	˚C	1.6mm (0.063”) from case for 10s	
T_M	Mounting torque	8	n	M3 or 6-32 screw	

Datasheet

Q_{gs}	Gate source charge	-	22	-	nC	V_{DS} = 800V, V_{GS} = -4/+18V I_D = 32A	Fig.12
Q_{gd}	Gate drain charge	-	18	-			
Q_g	Gate charge	-	60	-			

(Tc = 25°C unless otherwise specified)

E_{on} Turn on



Figure 1. Output characteristics T_J = -55 ºC

Figure 2. Output characteristics T_J = 25 ºC

Datas




Figure 19. Continuous drain current derating vs. case temperature




Figure 20. Maximum power dissipation derating vs. case temperature




Figure 21. Transient thermal impedance (junction - case)




Figure 22. Safe operating area




Figure 23. Clamped Inductive switching energy vs. drain current (V_{DD} = 600V)




Figure 24. Clamped inductive switching energy vs. drain current (V_{DD} = 800V)




Figure 25. Clamped inductive switching energy vs. R_G(ext)




Figure 26. Clamped inductive switching energy vs. temperature




Figure 27. Switching times vs. R_G(ext)

		——	——
		——	——
			——

1.
The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/ EC (RoHS2), as implemented January 2, 2013.

2.
REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Sichain representative to insure you get the most up-to-date REACh SVHC Declaration. REACh banned substance information (REACh Article 67) is also available upon request.

3. With respect to information regarding the application of the product, Sichain hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

4. Any information given in this documents subject to customer's compliance with its obligations and any applicable legal requirements, norms and standards concerning any use of the product of Sichain in any customer's applications.

5. Specifications of any and all products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance,characteristics,and functions of the described products as mounted in the customer's products or equipment.

6. Due to technical requirements products may contain dangerous substances. For information on the types in question please contact Sichain office.

7. Except as otherwise explicitly approved by Sichain in a written document signed by authorized representatives of Sichain, Sichain' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

8. For use of our products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a Sichain representatives, for example but not limited to: transportation equipment,primary communication equipment,traffic lights,fire/crime prevention, safety equipment, medical systems, and power transmission systems.